

© EPODOC / EPO

PN - JP7253858 A 19951003  
PD - 1995-10-03  
PR - JP19940042746 19940314  
OPD - 1994-03-14  
TI - IMAGE FORMING DEVICE AND ITS CONTROL METHOD  
IN - SAKURA MASAYUKI  
PA - CANON KK  
IC - G06F3/12 ; B41J5/30

© WPI / DERWENT

TI - Control method for image formation device - operates printer according to image formation instruction from computer  
PR - JP19940042746 19940314  
PN - JP7253858 A 19951003 DW199549 G06F3/12 006pp  
PA - (CANO ) CANON KK  
IC - B41J5/30 ;G06F3/12  
AB - J07253858 The control method involves sending of a printer lock command from a network 2) to a printer (7). The lock completion is acknowledged to a computer (1) which had passed to the lock command by the printer. The printer then weights for lock release command from the same computer, until which the time printing instructions from other computers are put in stand-by state.  
- USE/ADVANTAGE - In computer network. Facilitates image formation to be performed according to users requirement.  
- (Dwg.1/4)  
OPD - 1994-03-14  
AN - 1995-377860 [49]

© PAJ / JPO

PN - JP7253858 A 19951003  
PD - 1995-10-03  
AP - JP19940042746 19940314  
IN - SAKURA MASAYUKI  
PA - CANON INC  
TI - IMAGE FORMING DEVICE AND ITS CONTROL METHOD  
AB - PURPOSE:To form an image by a paper feed method desired by the user by receiving only an image forming instruction publicated from a publication source of a command and forming the image according to the image forming instruction upon the receipt of a